



Premium Quality



Dependable Performance



Outstanding Value

Compressed Air System Packages



Compressed Air
System Packages

These packages are recommended for premium industrial compressed air systems up to 1.75 m³/min. Each comprises an Airmac reciprocating compressor, refrigerant dryer and two stages of filtration. The clean, dry compressed air is suitable for pneumatic tools and machinery and also for spray painting.



T20 415V PRO PKG

HT20 415V PRO PKG

B23 415V PRO PKG

Air Compressor	AM T20 415V	AM HT20 415V	AM B23 415V
Motor Power	2.2 kW (3 hp)	2.2 kW (3 hp)	3 kW (4 hp)
Free Air Delivery	310 L/min (11.0 cfm)	260 L/min (9.2 cfm)	325 L/min (11.5 cfm)
Maximum Pressure	1,000 kPa (145 psi)	1,200 kPa (175 psi)	1,200 kPa (175 psi)
Pre Filter	T5P, 3 Micron Particulate	T5P, 3 Micron Particulate	T5P, 3 Micron Particulate
Refrigerant Dryer	Fusheng FR005A	SMC IDFA4E-23-LR	SMC IDFA4E-23-LR
Post Filter	T5U, 1 Micron Coalescing	T5U, 1 Micron Coalescing	T5U, 1 Micron Coalescing
Product Code	AM T20 415V PKG	AM HT20 415V PKG	AM B23 415V PKG



V25 415V PRO PKG

B29 415V PRO PKG

T30 415V PRO PKG

Air Compressor	AM V25 415V	AM B29 415V	AM T30 415V
Motor Power	3 kW (4 hp)	4 kW (5.5 hp)	4 kW (5.5 hp)
Free Air Delivery	465 L/min (16.4 cfm)	555 L/min (19.6 cfm)	620 L/min (21.9 cfm)
Maximum Pressure	1,000 kPa (145 psi)	1,200 kPa (175 psi)	1,000 kPa (145 psi)
Pre Filter	T5P, 3 Micron Particulate	T5P, 3 Micron Particulate	T5P, 3 Micron Particulate
Refrigerant Dryer	Fusheng FR005A	SMC IDFA4E-23-LR	Fusheng FR005A
Post Filter	T5U, 1 Micron Coalescing	T5U, 1 Micron Coalescing	T5U, 1 Micron Coalescing
Product Code	AM V25 415V PKG	AM B29 415V PKG	AM T30 415V PKG



V40 415V PRO PKG

B52 415V PRO PKG

T55 415V PRO PKG

Air Compressor	AM V40 415V	AM B52 415V	AM T55 415V
Motor Power	5.5 kW (7.5 hp)	7.5 kW (10 hp)	7.5 kW (10 hp)
Free Air Delivery	825 L/min (29.2 cfm)	1,050 L/min (37.1 cfm)	1,245 L/min (44.0 cfm)
Maximum Pressure	1,000 kPa (145 psi)	1,200 kPa (175 psi)	1,000 kPa (145 psi)
Pre Filter	T10P, 3 Micron Particulate	T10P, 3 Micron Particulate	T10P, 3 Micron Particulate
Refrigerant Dryer	Fusheng FR010A	SMC IDFA8E-23-LR	Fusheng FR010A
Post Filter	T10U, 1 Micron Coalescing	T10U, 1 Micron Coalescing	T10U, 1 Micron Coalescing
Product Code	AM V40 415V PKG	AM B52 415V PKG	AM T55 415V PKG



T75 415V PRO PKG

Air Compressor	AM T75 415V
Motor Power	11 kW (15 hp)
Free Air Delivery	1,750 L/min (61.8 cfm)
Maximum Pressure	1,000 kPa (145 psi)
Pre Filter	T15P, 3 Micron Particulate
Refrigerant Dryer	Fusheng FR020A
Post Filter	T15U, 1 Micron Coalescing
Product Code	AM T75 415V PKG

For special applications requiring clean, odourless and oil free compressed air up to 0.9 m³/min. These packages include an Airmac oil-less compressor, refrigerant dryer and four stages of filtration. Typical users include food and pharmaceutical manufacturers, hospitals and hazardous coating applicators.



V30-OF ULT PKG

T40-OF ULT PKG

T55-OF ULT PKG

Air Compressor	AM V30 Oil Free	AM T40 Oil Free	AM T55 Oil Free
Motor Power	4 kW (5.5 hp)	5.5 kW (7.5 hp)	7.5 kW (10 hp)
Free Air Delivery	510 L/min (18.0 cfm)	690 L/min (24.4 cfm)	900 L/min (31.8 cfm)
Pre Filter	T5P, 3 Micron Particulate	T10P, 3 Micron Particulate	T10P, 3 Micron Particulate
Refrigerant Dryer	FR005A	FR010A	FR010A
Post Filter #1	T5U, 1 Micron Coalescing	T10U, 1 Micron Coalescing	T10U, 1 Micron Coalescing
Post Filter #2	T5H, 0.01 Micron Coalescing	T10H, 0.01 Micron Coalescing	T10H, 0.01 Micron Coalescing
Post Filter #3	T5C, Activated Carbon	T10C, Activated Carbon	T10C, Activated Carbon
Product Code	AM V30-OF PKG	AM T40-OF PKG	AM T55-OF PKG

A popular choice for industrial applications with compressed air demand of up to 1.52 m³/min. Each package features a Puma reciprocating compressor, refrigerant dryer and two stages of filtration. The clean, dry compressed air is suitable for powering pneumatic tools and machinery and also for spray painting.



P25 415V PRO PKG

P30 415V PRO PKG

P40 415V PRO PKG

Air Compressor	PU P25 415V	PU P30 415V	PU P40 415V
Motor Power	3 kW (4 hp)	4 kW (5.5 hp)	5.5 kW (7.5 hp)
Free Air Delivery	390 L/min (13.8 cfm)	520 L/min (18.4 cfm)	760 L/min (26.9 cfm)
Maximum Pressure	900 kPa (130 psi)	900 kPa (130 psi)	900 kPa (130 psi)
Pre Filter	T5P, 3 Micron Particulate	T5P, 3 Micron Particulate	T10P, 3 Micron Particulate
Refrigerant Dryer	FR005A	FR005A	FR010A
Post Filter	T5U, 1 Micron Coalescing	T5U, 1 Micron Coalescing	T10U, 1 Micron Coalescing
Product Code	PU P25 415V PKG	PU P30 415V PKG	PU P40 415V PKG



P55 415V PRO PKG

P75 415V PRO PKG

Air Compressor	PU P55 415V	PU P75 415V
Motor Power	7.5 kW (10 hp)	11 kW (15 hp)
Free Air Delivery	1,055 L/min (37.3 cfm)	1,520 L/min (53.7 cfm)
Maximum Pressure	900 kPa (130 psi)	900 kPa (130 psi)
Pre Filter	T10P, 3 Micron Particulate	T15P, 3 Micron Particulate
Refrigerant Dryer	FR010A	FR020A
Post Filter	T10U, 1 Micron Coalescing	T15U, 1 Micron Coalescing
Product Code	PU P55 415V PKG	PU P75 415V PKG

Ideal for noise sensitive workplace applications up to 1.1 m³/min where there is no need for treatment of the compressed air, such as air cleaning and dusting, pneumatic transfer pumping and liquid waste aeration. Each package comprises a Puma 415 Volt Silent reciprocating air compressor and vertical air receiver.



P30S 415V BAS PKG

P40S 415V BAS PKG

P55S 415V BAS PKG

Air Compressor	PU P30S 415V	PU P40S 415V	PU P55S 415V
Motor Power	4 kW (5.5 hp)	5.5 kW (7.5 hp)	7.5 kW (10 hp)
Free Air Delivery	520 L/min (18.4 cfm)	760 L/min (26.9 cfm)	1,055 L/min (37.3 cfm)
Maximum Pressure	930 kPa (135 psi)	930 kPa (135 psi)	930 kPa (135 psi)
Vertical Air Receiver	300 Litres c/w Accessory Kit	300 Litres c/w Accessory Kit	300 Litres c/w Accessory Kit
Product Code	PU P30S 415V BPG	PU P40S 415V BPG	PU P55S 415V BPG

These packages are ideal for low noise workplace applications requiring up to 1.1 m³/min of clean, dry compressed air. A Puma 415 Volt Silent reciprocating air compressor, vertical air receiver, refrigerant dryer and two stages of filtration are included. Suitable for use with pneumatic tools / machinery and for spray painting.



P30S 415V PRO PKG

P40S 415V PRO PKG

P55S 415V PRO PKG

Air Compressor	PU P30S 415V	PU P40S 415V	PU P55S 415V
Motor Power	4 kW (5.5 hp)	5.5 kW (7.5 hp)	7.5 kW (10 hp)
Free Air Delivery	520 L/min (18.4 cfm)	760 L/min (26.9 cfm)	1,055 L/min (37.3 cfm)
Maximum Pressure	930 kPa (135 psi)	930 kPa (135 psi)	930 kPa (135 psi)
Vertical Air Receiver	300 Litres c/w Accessory Kit	300 Litres c/w Accessory Kit	300 Litres c/w Accessory Kit
Pre Filter	T5P, 3 Micron Particulate	T10P, 3 Micron Particulate	T10P, 3 Micron Particulate
Refrigerant Dryer	FR005A	FR010A	FR010A
Post Filter	T5U, 1 Micron Coalescing	T10U, 1 Micron Coalescing	T10U, 1 Micron Coalescing
Product Code	PU P30S 415V PKG	PU P40S 415V PKG	PU P55S 415V PKG

The premium value choice for standard industrial compressed air systems in the 0.6 to 2.45 m³/min range. Each package includes a Senator ES Series tank-mounted screw compressor, refrigerant dryer and two stages of filtration. The clean, dry compressed air is suitable for most pneumatic applications.



ES4 PRO PKG

ES5 PRO PKG

ES7 PRO PKG

Air Compressor	SE ES4-8	SE ES5-8	SE ES7-8
Motor Power	4 kW (5.5 hp)	5.5 kW (7.5 hp)	7.5 kW (10 hp)
Free Air Delivery	0.60 m ³ /min (21 cfm)	0.82 m ³ /min (29 cfm)	1.10 m ³ /min (39 cfm)
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Tank Volume	250 Litres	250 Litres	250 Litres
Pre Filter	T5U, 1 Micron Coalescing	T10U, 1 Micron Coalescing	T10U, 1 Micron Coalescing
Refrigerant Dryer	FR005A	FR010A	FR010A
Post Filter	T5H, 0.01 Micron Coalescing	T10H, 0.01 Micron Coalescing	T10H, 0.01 Micron Coalescing
Product Code	SE ES4-8 PKG	SE ES5-8 PKG	SE ES7-8 PKG



ES11 PRO PKG

ES15 PRO PKG

Air Compressor	SE ES11-8	SE ES15-8
Motor Power	11 kW (15 hp)	15 kW (20 hp)
Free Air Delivery	1.78 m ³ /min (63 cfm)	2.45 m ³ /min (87 cfm)
Working Pressure	8 bar (116 psi)	8 bar (116 psi)
Tank Volume	350 Litres	350 Litres
Pre Filter	T15U, 1 Micron Coalescing	T20U, 1 Micron Coalescing
Refrigerant Dryer	FR020A	FR020A
Post Filter	T15H, 0.01 Micron Coalescing	T20H, 0.01 Micron Coalescing
Product Code	SE ES11-8 PKG	SE ES15-8 PKG

The smart value choice for energy saving compressed air systems in the 1.10 to 2.45 m³/min range. Each package includes a Senator ESV Series variable speed screw compressor, refrigerant dryer and two stages of filtration. The clean, dry compressed air is suitable for most pneumatic applications.



ESV7 PRO PKG

ESV11 PRO PKG

ESV15 PRO PKG

Air Compressor	SE ESV7-8	SE ESV11-8	SE ZS200T
Motor Power	7.5 kW (10 hp)	11 kW (15 hp)	15 kW (20 hp)
Free Air Delivery	0.44 - 1.10 m ³ /min (16 - 39 cfm)	0.71 - 1.78 m ³ /min (25 - 63 cfm)	0.98 - 2.45 m ³ /min (35 - 87 cfm)
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Tank Volume	250 Litres	350 Litres	350 Litres
Pre Filter	T10U, 1 Micron Coalescing	T15U, 1 Micron Coalescing	T20U, 1 Micron Coalescing
Refrigerant Dryer	FR010A	FR020A	FR020A
Post Filter	T10H, 0.01 Micron Coalescing	T15H, 0.01 Micron Coalescing	T20H, 0.01 Micron Coalescing
Product Code	SE ESV7-8 PKG	SE ESV11-8 PKG	SE ESV15-8 PKG

Recommended for industrial applications with stable compressed air demand up to 12.33 m³/min. Each package comprises a Senator LS Series screw compressor, vertical air receiver, refrigerant dryer and two stages of filtration. Users can depend on these for clean, dry compressed air and low operating noise level.


LS18 PRO PKG
LS22 PRO PKG
LS30 PRO PKG

Air Compressor	SE LS18-8	SE LS22-8	SE LS30-8
Motor Power	18.5 kW (25 hp)	22 kW (30 hp)	30 kW (40 hp)
Free Air Delivery	3.08 m ³ /min (109 cfm)	3.58 m ³ /min (127 cfm)	4.96 m ³ /min (175 cfm)
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Vertical Air Receiver	300 Litres c/w Accessory Kit	530 Litres c/w Accessory Kit	530 Litres c/w Accessory Kit
Pre Filter	T40U, 1 Micron Coalescing	T40U, 1 Micron Coalescing	T40U, 1 Micron Coalescing
Refrigerant Dryer	FR030A	FR030A	FR050A
Post Filter	T40H, 0.01 Micron Coalescing	T40H, 0.01 Micron Coalescing	T40H, 0.01 Micron Coalescing
Product Code	SE LS18-8 PKG	SE LS22-8 PKG	SE LS30-8 PKG


LS37 PRO PKG
LS45 PRO PKG
LS55 PRO PKG

Air Compressor	SE LS37-8	SE LS45-8	SE LS55-8
Motor Power	37 kW (50 hp)	45 kW (60 hp)	55 kW (75 hp)
Free Air Delivery	6.38 m ³ /min (225 cfm)	7.18 m ³ /min (254 cfm)	9.58 m ³ /min (338 cfm)
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Vertical Air Receiver	820 Litres c/w Accessory Kit	820 Litres c/w Accessory Kit	1,240 Litres c/w Accessory Kit
Pre Filter	T60U, 1 Micron Coalescing	T60U, 1 Micron Coalescing	T75U, 1 Micron Coalescing
Refrigerant Dryer	FR050A	FR075A	FR075A
Post Filter	T60H, 0.01 Micron Coalescing	T60H, 0.01 Micron Coalescing	T75H, 0.01 Micron Coalescing
Product Code	SE LS37-8 PKG	SE LS45-8 PKG	SE LS55-8 PKG

**LS75 PRO PKG**

Air Compressor	SE LS75-8
Motor Power	75 kW (100 hp)
Free Air Delivery	12.33 m ³ /min (435 cfm)
Working Pressure	8 bar (116 psi)
Vertical Air Receiver	1,240 Litres c/w Accessory Kit
Pre Filter	T125U, 1 Micron Coalescing
Refrigerant Dryer	FR100A
Post Filter	T125H, 0.01 Micron Coalescing
Product Code	SE LS75-8 PKG

The smart energy saving solution for industrial applications with fluctuating compressed air demand up to 12.33 m³/min. Each package comprises a Senator LSV Series variable speed screw compressor, vertical air receiver, refrigerant dryer and two stages of filtration. Clean, dry compressed air at the lowest overall cost.



LSV18 PRO PKG

LSV22 PRO PKG

LSV30 PRO PKG

Air Compressor	SE LSV18-8	SE LSV22-8	SE LSV30-8
Motor Power	18.5 kW (25 hp)	22 kW (30 hp)	30 kW (40 hp)
Free Air Delivery	1.08 - 3.08 m ³ /min	1.25 - 3.58 m ³ /min	1.74 - 4.96 m ³ /min
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Vertical Air Receiver	300 Litres c/w Accessory Kit	530 Litres c/w Accessory Kit	530 Litres c/w Accessory Kit
Pre Filter	T40U, 1 Micron Coalescing	T40U, 1 Micron Coalescing	T40U, 1 Micron Coalescing
Refrigerant Dryer	FR030A	FR030A	FR050A
Post Filter	T40H, 0.01 Micron Coalescing	T40H, 0.01 Micron Coalescing	T40H, 0.01 Micron Coalescing
Product Code	SE LSV18-8 PKG	SE LSV22-8 PKG	SE LSV30-8 PKG



LSV37 PRO PKG

LSV45 PRO PKG

LSV55 PRO PKG

Air Compressor	SE LSV37-8	SE LSV45-8	SE LSV55-8
Motor Power	37 kW (50 hp)	45 kW (60 hp)	55 kW (75 hp)
Free Air Delivery	2.23 - 6.38 m ³ /min	2.51 - 7.18 m ³ /min	3.35 - 9.58 m ³ /min
Working Pressure	8 bar (116 psi)	8 bar (116 psi)	8 bar (116 psi)
Vertical Air Receiver	820 Litres c/w Accessory Kit	820 Litres c/w Accessory Kit	1,240 Litres c/w Accessory Kit
Pre Filter	T60U, 1 Micron Coalescing	T60U, 1 Micron Coalescing	T75U, 1 Micron Coalescing
Refrigerant Dryer	FR050A	FR075A	FR075A
Post Filter	T60H, 0.01 Micron Coalescing	T60H, 0.01 Micron Coalescing	T75H, 0.01 Micron Coalescing
Product Code	SE LSV37-8 PKG	SE LSV45-8 PKG	SE LSV55-8 PKG

**LSV75 PRO PKG**

Air Compressor	SE LSV75-8
Motor Power	75 kW (100 hp)
Free Air Delivery	4.32 - 12.33 m ³ /min
Working Pressure	8 bar (116 psi)
Vertical Air Receiver	1,240 Litres c/w Accessory Kit
Pre Filter	T125U, 1 Micron Coalescing
Refrigerant Dryer	FR100A
Post Filter	T125H, 0.01 Micron Coalescing
Product Code	SE LSV75-8 PKG

