



Westinghouse

INNOVATION YOU CAN BE SURE OF

WHXC8500E

Portable Generator

Westinghouse Utility Series generators are compact, high performance units designed specifically for Australian operating conditions. Equipped with a unique combination of premium quality features, they offer superior value for money and are an ideal backup power supply for your home, business or farm.

Features and Benefits

Reliable Performance

High output and fuel efficient Westinghouse 420 cc 4-stroke overhead valve petrol engine.

Effortless Starting

Strain-free electric starting at the push of a button. Heavy duty 12 Volt battery included.

Quiet Operation

Oversized Pulse-Flo muffler and anti-vibration rubber mounts ensure low noise output.

Long Running

Extended run time from the long range 25 litre fuel tank with integrated gauge and strainer.

Stable Power

Digital AVR controlled sine wave output for precise and stable electricity supply.

Premium Features

Copper wound alternator, full steel roll frame, fold-down handles and Never-Flat wheels.

Clean Air Technology

Compliant with Australian and US EPA emissions standards to minimise environmental impact.

Easy to Use

Yellow-coloured touch points guide you to the controls required for normal operation.

Plug and Play

Everything you need is in the box. Just add petrol. Minor assembly required.

Warranty Protection

2-year domestic use warranty to safeguard your investment (conditions apply).

6750/8500*

RUNNING WATTS STARTING WATTS
*10.6 kVA @ 0.8 PF



Control Panel Functions



Power - when you need it - where you need it

Specifications

WHXC8500E

ENGINE	
Type	1-Cylinder, 4-Stroke, Overhead Valve, Air Cooled
Displacement (cc)	420
Max. Speed (rpm)	3,000
Rated Power (kW / hp)	9.5 / 12.7
Oil Capacity (mL)	1,000
Low Oil Shutdown	Yes
Spark Plug	Torch F6RTC
Fuel	Unleaded Petrol
Fuel Tank Capacity (L)	25
Fuel Gauge	Yes
Starting Methods	Electric and Recoil
Battery	12 V, Maintenance Free
Hour Meter	Yes
Run Time @ 50% Output (hr)	13.1
Noise Level @ 100% Output	80 dB(A) @ 7m
DIMENSIONS	
Length (mm)	735
Width (mm)	700
Height (mm)	655
WEIGHT	
Weight - Dry (kg)	94
Weight - Wet (kg)	113

240 VOLT AC ELECTRICAL	
Voltage (V)	240
Frequency (Hz)	50
No. of Phases	1
Running Power (W)	6,750
Starting Power (W)	8,500
Max. Output @ 0.8 PF (kVA) *	10.6
Max. Running Current (A)	28.1
Max. Starting Current (A)	35.4
Alternator Windings	Copper
Voltage & Waveform Control	Digital Automatic Voltage Regulator Sine Wave Output
Receptacles	2 x 15 A, IP44
Overload Protection	Circuit Breaker
Digital VFT Meter	Yes
Electrical Enclosure	IP23
12 VOLT DC ELECTRICAL	
Voltage (V)	12
Maximum Current (A)	8.3
Maximum Power (W)	100

* Theoretical value for comparison.

Specifications are subject to change without notice. 2019-02



Westinghouse

INNOVATION YOU CAN BE SURE OF

westinghousepower.com.au